



Link Bar

These are passive units that facilitate the interconnection of low voltage circuits. They are rated at 15A max per channel. There are 2 variants a 120mm, 10 way model and a 50mm, 4 way version. They are designed to simplify wiring installations and to improve safety and security.

Variants

Base Colours :	White, Green
Length :	50mm, 120mm
Rating :	15A
Connections :	Screw

Product Information

Size WxH :	50mm x 43mm <small>(L = 50, 120mm)</small>
Weight 50/120	40gm/225gm
Composition :	Plastic & Steel
Made In :	United Kingdom
Software :	None
Packed Weight :	+90gm for P&P
Warranty :	10 years
Made By :	Smart Boat Ltd

Flexible Mounting Options: Easily mount on DIN rails or any surface with the four stainless steel fixing screws provided.

Efficient Wiring Design: Incorporating a Smart Wiring Link Bar simplifies building and designing wiring circuits, making equipment servicing, replacement, and repair significantly easier and more flexible, thus saving time and effort.

High Current Capacity: Innovative PCB design supports a 15A rating for each circuit.

Versatile Circuit Options: Available in 4 or 10 circuit configurations to suit various needs.

Enhanced Protection: Removable clip-on cover prevents shorting events and protects installations in dirty environments.

Clear Identification: Comes with preprinted labels featuring 96 different circuit names for clear wiring installation schemas, specifically designed for boat and RV markets.

Detailed Labelling: Includes name labels for the base of the Link Bar to identify circuit modules, such as +12V or Bilge Pump.

Eco-Friendly Materials: Base made from sustainable biomass to minimize environmental impact.

Durable Fasteners: All fasteners are made from stainless steel to avoid corrosion, with through bolts providing maximum protection from vibration and harsh environments. Terminals are fitted with washers and spring washers to ensure secure connections.

